## HYDROGEN STORAGE PERFORMANCE OF ACTIVATED NATURAL ZEOLITE AND ITS MODIFICATION WITH ACTIVATED CHARCOAL

Latifah Hauli <sup>©a\*</sup>, Chika Lutfi Adiningrum <sup>b</sup>, Muhammad Safaat <sup>©a</sup>, Indri Badria Adilina <sup>a</sup>, Silvester Tursiloadi <sup>©a</sup>, Lenny Marlinda <sup>©b</sup>, Dian Susanthy <sup>©c</sup>, Muflikhah Muflikhah <sup>©d</sup>

<sup>a</sup>Research Center for Chemistry, National Research and Innovation Agency (BRIN), B.J. Habibie Science and

Technology Area, 60, Raya Puspiptek str., Setu, South Tangerang, Banten 15314, Indonesia <sup>b</sup>Department of Chemistry, Faculty of Science and Technology, Universitas Jambi,

Department of Chemistry, Faculty of Science and Technology, Universitas Jambi,

15, Jambi-Muara Bulian No.KM. str., Jambi Luar Kota, Muaro Jambi, Jambi 36361, Indonesia

<sup>c</sup>Department of Chemistry, Faculty of Mathematics and Natural Sciences, Universitas Gadjah Mada,

Bulaksumur, Depok, Sleman, Yogyakarta 55281, Indonesia

<sup>d</sup>Research Center for Radiation Detection and Nuclear Analysis Technology, National Research and Innovation

Agency (BRIN), B.J. Habibie Science and Technology Area, 60, Raya Puspiptek str., Setu, South Tangerang 15314, Indonesia

e-mail: latifah.hauli@brin.go.id

**Abstract.** The modification of zeolite with activated charcoal for hydrogen adsorption was investigated. The aims of this research were to activate natural zeolite (Z), modify Z with commercial activated charcoal (AC/Z), and study the properties of these materials for hydrogen storage. The Z was prepared by the desilication method. The obtained Z was modified by activated charcoal using the wet impregnation method. The obtained materials were characterised by surface area analyser, X-ray diffraction, fourier transform infrared spectroscopy, and scanning electron microscopy with energy dispersive spectrometry. The hydrogen storage performance (at 298 K and 1 atm) was observed by Hydrogen-temperature programmed desorption (H<sub>2</sub>-TPD). The results showed that the presence of activated charcoal on the zeolite surface increased the specific surface area, reached 188.54 m<sup>2</sup>/g. However, Z exhibited the highest hydrogen storage capacity of 0.57 mmol/g.

Keywords: zeolite, activated charcoal, adsorbent, hydrogen storage.

Received: 30 January 2025/ Revised final: 29 April 2025/ Accepted: 2 May 2025